

## OMNIKEY® 3921 PC Built-In USB Reader



### PC BUILT-IN USB READER

- **Plug-and-Play** – Designed to facilitate easy device installation with high-quality drivers\* for all major PC operating systems
- **Readily Compliant** – Meets all relevant industry standards for smooth integration in PC environment
- **Installation Ready** – Designed for integration into standard 3.5" floppy disk bay
- **Suits Any Application** – Compatible with virtually any contact smart card and major PC operating system


The OMNIKEY® 3921 is a high-performance, built-in, Plug and Play USB reader that can be easily integrated into the 3.5" floppy bay housing within a desktop computer. Featuring a transmission speed to the card of up to 420kbps, the OMNIKEY 3921 reader is compliant with all relevant industry standards.

Compatible with virtually any contact smart card or operating system, as well as a variety of applications, this easy-to-install OMNIKEY reader is well-suited for a wide range of smart card operations, including single sign-on, online-banking or digital signature applications.

\* For driver download, please visit [www.omnikey.com](http://www.omnikey.com).

## FEATURES:

- Meets major standards, including ISO 7816, EMV 2000, Microsoft® WHQL, USB CCID, PC / SC and HBCI (Home Banking Computer Interface)
- Usage within an application is based on standardized interfaces like PC / SC, OCF (Open Card Framework) or CT-API
- Available in a bulk version with internal USB cable for main board connector or as retail version with internal and external USB cable, slot bracket, driver CD and mounting screws
- USB CCID support makes integration into an existing system the easiest ever by connecting host and smart card reader without the need for additional drivers
- All major operating systems supported
- Meets GSA FIPS 201 requirements
- Supports high-speed data transmission



## SPECIFICATIONS

<b>Base Model Number</b>	OMNIKEY® 3621
<b>Dimensions</b>	5.51" x 3.14" x 1.97" (140 x 80 x 50 mm)
<b>Weight (with cable)</b>	6.1 oz (173 g)
<b>Power Supply</b>	Bus powered
<b>Operating Temperature</b>	32-131 °F (0-55 °C)
<b>Operating Humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 CCID <sup>1</sup> (also compliant with USB 1.1)
<b>Transmission Speed</b>	12 Mbps (USB 2.0 full speed)
<b>SMART CARD INTERFACE</b>	
<b>Standards</b>	ISO 7816 & EMV <sup>2</sup> 2000 Level 1
<b>Protocols</b>	T=0, T=1, 2-wire: SLE 4432/42 (S=10); 3-wire: SLE 4418/28 (S=9), I <sup>2</sup> C (S=8)
<b>Card Size</b>	ID-1 (full size)
<b>Smart Card Interface Speed</b>	420 Kbps (when supported by card)
<b>Smart Card Clock Frequency</b>	Up to 8 MHz
<b>Supported Card Types</b>	5V, 3V and 1.8V Smart Cards, ISO 7816 Class A, B and C
<b>Power to Smart Card</b>	60 mA
<b>Smart Card Detection</b>	Movement detection with auto power-off / Automatic detection of smart card type / Short circuit and thermal protection
<b>8-Pin Handling</b>	C4 / C8 supported
<b>Supported APIs</b>	PC / SC driver (ready for 2.0), CT-API (on top of PC / SC), Synchronous-API (on top of PC / SC), OCF (on top of PC / SC),
<b>PC / SC Driver Support</b>	Windows® 2000 / XP (32 bit), 2003 Server, 2008 Server, Windows® CE 5.0 / CE.NET / CE 6.0 (depending on hardware), Windows® XP (64 bit), Windows® Vista (32 bit / 64 bit), Windows 7 (32 bit / 64 bit), Linux®, Mac® OS X (Power PC / Intel)
<b>Embedded Technology</b>	OMNIKEY® Smart@Link Chipset
<b>Status Indicator</b>	Green LED
<b>Reader Board</b>	Also available as PCB
<b>Color</b>	Dark gray
<b>Options</b>	Customer-specific logo, label and colors: available upon request
<b>Composition</b>	ABS
<b>Connector Cable</b>	External: 59.1" (150 cm) Internal: 31.5" (80 cm)
<b>Durability</b>	100,000 insertions
<b>Meantime Between Failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>3</sup> , EMV <sup>2</sup> 2000 Level 1, ISO 7816, HBCI <sup>4</sup> , USB 2.0 (USB 1.1 compatible), CCID <sup>1</sup> , Common Criteria EAL 3+, GSA FIPS 201 approved product list
<b>Safety / Environmental</b>	CE, WEEE, FCC, UL, RoHS
<b>Warranty</b>	Two-year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

1 = Chip Card Interface Device, 2 = Europay® MasterCard® Visa®, 3 = Windows® Hardware Quality Lab, 4 = Homebanking Computer Interface

North America: +1 949 732 2000  
Toll Free: 1 800 237 7769  
Europe, Middle East, Africa: +44 1440 714 850  
Asia Pacific: +852 3160 9800  
Latin America: +52 55 5081 1650

hidglobal.com

## ASSA ABLOY

An ASSA ABLOY Group brand

© 2011 HID Global Corporation. All rights reserved. HID, the HID logo, OMNIKEY and the OMNIKEY logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks and product or service names are trademarks or registered trademarks of their respective owners.  
2011-07-11-omnikey-3921-pc-built-in-reader-ds-en